

Mac SCX

Self Contained Compactor

Standard Features

Key-lock Start Switch.	Power Unit Weather Cover.
Reverse Push Button	Power Unit Factory Ready for 208-230-460 Volt 3 phase.
Red Mushroom-head Stop Button.	Automatic Motor Starter Reset.
Solid State Motor Starter Overload. Adjustable 9-45 Amp.	
NEMA 12/13 Panel Box.	

Mfr. Rating	3 cubic yards	Cycle Time	48 seconds
Industry Rating	2.7 cubic yards	Motor	15 H.P. TEFC
Clear Top Opening	59" x 70"	Pump	13 GPM vane
Hydraulic Cylinders	(2) 4-1/2" bore x 2-1/2" rod	Frame Floor	3/8" plate
Ram Penetration	10"	Frame Sides	3/8" plate
Packing Force	Normal: 58,300 lbs. Maximum Pack-Out: 62,400 lbs.	Breaker Bar	8" x 6" x 3/4" angle
Ram Face PSI	Normal: 27 PSI Maximum: 25.35 PSI	Ram Face	1/2" plate
Hydraulic Pressure	Normal: 2150 PSI Maximum: 2300 PSI	Ram Floor	1/2" plate
Ram Face Dimensions	30" x 72"	Ram Top	1/4" plate
		Ram Sides	1/4" plate
		Ram Guides (4)	UHMWPE

4717 Massachusetts Avenue
Indianapolis, Indiana
317-545-3341
800-447-5205
Fax: 317-545-8760